



SURFACE MOUNTING

- Self-locking, electromechanical operator, reliable and silent
- Reduced dimensions
- Easy and fast to install thanks to the front articulation and to the two mechanical stops, adjustable both in opening and closing phases
- Strong and reliable rolled worm shaft with \varnothing 20mm spherical section for a silent movement and easy manual operation



BOB30M up to 3 m

INSTALLATION LIMITS

LEAF DIMENSION	MAX. WEIGHT
1,5m**	400 kg
1,8m**	350 kg
2,1m**	300 kg
2,5m	250 kg
3,0m	200 kg

** With BOB.SL



AUTOMATIONS FOR SWINGING GATES

TECHNICAL DATA	BOB30M
Power supply	230 Vac
Motor supply	230 Vac
Max. absorbed current	1.8 A
Thrust	2300 N
Opening time	18"
Operation cycle	30%
Standard stroke	270 mm
Max stroke	325 mm
Protection level	IP 44
Operating temp.	-20°C / +50°C
Weight	8.2 kg

*INSTALLATION MEASUREMENTS WITH BOB.SL

Using BOB.SL bracket you can have an increase of 15% in the leaf performances



Innovative FACE pair of gears.
Mechanics all in metal.
(Patent Pending)



High quality materials, gear and female screw in bronze



Unlock device operating from the top, very fast and easy to use.



Built-in lock with personalized key

