



Made in
Italy

SURFACE MOUNTING

- 230 Vac self-locking electromechanical operator
- Strong definition motor made in Italy, combining high performance, quality and reliability
- Innovative anti-corrosion treatment greatly increasing resistance to atmospheric agents over time.

BOB50M up to 5 m




INSTALLATION LIMITS	BOB50ME
2,5m	800 kg
3,0m	700 kg
3,5m	500 kg
4,0m*	450 kg
4,5m*	400 kg
5,0m*	350 kg

* For leaves longer than 4m we advise to install an electric lock



AUTOMATIONS FOR SWINGING GATES

TECHNICAL DATA	BOB50M
Power supply	230 Vac
Motor supply	230 Vac
Max. absorbed current	1.4 A
Thrust	3500 N
Opening time	26"
Operation cycle	30%
Standard stroke	455 mm
Max stroke	520 mm
Protection level	IP 44
Operating temp.	-20°C / +50°C
Weight	11.6 kg



Release system with a hexagonal key, protected by an aluminum door opened with a customized key.



Innovative FAGO pair of gears. Mechanics all in metal. Patent Pending.



High quality materials, gear and female screw in bronze, worm screw in steel.



Quick and easy installation thanks to the tapered shape and reduced size (only 70 mm on wall).

MEASURES

	A	B
BOB50M/BOB504	150/225	150/225

