



ISO 9001:2000



## JIM.3 RESIDENTIAL AND COMMERCIAL USE BELT DRIVE

- 24 Vdc self-locking electromechanical operator for residential sectional garage doors
- Encoder device for the detection of obstacles integrated in the control panel
- Adjustable stroke by mechanical limits stop
- Built-in, low consumption LED courtesy light
- Operation continuity guaranteed in case of power failure with the battery back up unit integrable in the operator
- Self-Learning limit switches

## KEN.4 RESIDENTIAL AND COMMERCIAL USE CHAIN DRIVE

- Self-locking electromechanical operators for residential sectional garage doors
- Automation with a high safety level and intensive use
- Limit switch included
- Integrated courtesy light
- Equipped with control panel



### JIM.3



### KEN.4

## AUTOMATIONS FOR GARAGE & INDUSTRIAL DOORS

TECHNICAL DATA	JIM.3	KEN.4
Power supply	230 Vac	230 Vac
Motor supply	24 Vdc	24 Vdc
Max. absorbed current	0.7 A	1.5 A
Thrust	600 N	1200 N
Opening time	8.9 m/1'	8.0 m/1' - 6.0 m/1'
Operation cycle	intensive use	intensive use
Protection level	IP 40	IP 40
Limit switch	electronic with encoder	double microm.
Operating temp.	-20°C/+50°C	-20°C/+50°C
Max door surface	11 sqm/max	22 sqm/max
Rail	PTC.3/PTC.3/PTCL.4	PTN/PTL/PTE
Receiver	built-in	built-in
Weight	6.2 kg	7.6 kg
Items no. per pallet	50	50

